




PN: DG-LP91-20000-C13L16-808CJ

20000W QCW 1064nm

Macro-channel Semiconductor Laser Side Pump Module

宏通道半导体激光器侧泵模块



Version	Change Items	Released Date
Rev 1	Initial	2023.06.28

主要特性 Key Features:

- 金锡焊料封装 / AuSn packaging
- 高可靠性 / High reliability
- 长脉宽/ Long pulse-width operation

		Unit
Pump Power	20000	W
Peak Wavelength	808	nm
Optical Parameter		
Number of Bars	91	
Rod Material	Nd:YAG	
Rod Diameter	12	mm
Rod Length	191	mm
Rod Terminal	Flat / AR	
Electrical Parameter		
Operating Current	≤ 230	A
Threshold Current	30	A
Operating Voltage	182	V
Water Parameter		
cooling	Distilled Water	
Water Temperature(No Condensation)	23	°C
Water Pressure	≤ 0.45	MPa
Minimum Flow Rate	≥ 14	lpm
Storage Temperature	-45-85	°C
Operation Condition		
Pulse Width	us	200
Duty Cycle	%	5

输出功率测试条件：450mm±5mm 平平腔，输出镜透过率 30%。

备注：


¹ 在冷却水 23 摄氏度下测得。Tested at a cooling water temperature of 23°C.

² 在不结露条件下使用和存储。No-condensing required for operation and storage.

³ 超规格使用会导致激光器寿命下降。Reduced lifetime if used above nominal operating condition.

外形尺寸/ Dimension

DG-LP91-20000-C13L16-808CJ:



Customized dimension available upon request

使用说明 Application Notes:

- 叠阵输出激光会伤眼睛，使用时须遵守 IEC 四级激光标准安全规范，避免激光直接或间接照射眼睛；
The laser beam could hurt eyes, please follow the standard safety procedures for IEC Class 4 lasers, avoid eyes exposure to radiation.
- 静电击穿导致半导体激光器失效，激光器安装人员须经过培训，操作时须佩戴防静电手腕带，工作台需接地；在供电接头与激光器连接前，正负极应处于短接状态；
ESD cause diode laser failure, The operator should be trained, wearing ESD grounding straps and the work surface should be grounded. The positive and negative poles shall be connected before the power supply is connected with the laser.
- 电流过冲可能损坏激光器，驱动电源须稳定无过冲。
The current overshoot may damage the laser, and the driving power must be stable without overshoot,

