

Data Sheet

808nm 300mW VCSEL Moudle

Dogain Optoelectronic Technology(Suzhou)Co.,Ltd

PN: DG-VP-A808-300BS54A 模组

Rev. 1.0

Feb. 2026

Note:Customers represent that they have all the necessary expertise to createand implement their own safeguards that anticipate dangerous failures, monitor failures and their consequences,lessen the likelihood of dangerous failures and take appropriate remedial actions.

本文件及其披露的任何数据的所有权均属于度巨核芯光电技术（苏州）有限公司，构成并包含专有信息。除非度巨核芯光电技术（苏州）有限公司明确书面授权，否则不具有任何接收或拥有本文件授予或转让复制、使用或披露本文件所含任何信息的权利。

DG

REV: A0

商业秘密 Confidential document

Revision History			
Rev.	Effective Date	Revised By.	The Main Contents Revised.
A00	2026.02.26	Xiao bao Wan	Initial version released

本文件及其披露的任何数据的所有权均属于度巨核芯光电技术（苏州）有限公司，构成并包含专有信息。除非度巨核芯光电技术（苏州）有限公司明确书面授权，否则不具有任何接收或拥有本文件授予或转让复制、使用或披露本文件所含任何信息的权利。

DG

REV: A0

*商业秘密Confidential document

Product Introduction

Performance characteristics

- Wavelength: 808 nm
- Power: 240mW
- FOV: 130°

Absolution maximum ratings

Items	Values
Maximum reverse bias voltage	5 V
ESD threshold (Human body model)	1,000 V
Storage temperature range	-30 °C to 70 °C
Operation temperature range	-10 °C to 45 °C


Electro-optical characteristics (25°C)

	Parameters	Symbol	Unit	Min	Typical	Max	Notes
Electrical	Threshold Current	I_{th}	mA	-	35	-	#1, #2
	Forward Bias Current	I_0	mA	-	360	-	
	Forward Voltage	V_0	V	-	2.0	-	#1
Optical	Output Power	P	mW	200	240		#1
	Central Wavelength	λ_p	nm	800	808	816	#1
	Field of View	θ (X)	°	120	130	140	#1, #3
	Average Line Width	ω	mm	-	3	-	#1, #4, #5
	BOW	/	mm	-2.5	0	2.5	#1, #4, #5
	Rotation Angle	α	°	-1.5	0	1.5	#1, #5
	Pitch Angle	β	°	-1.5	0	1.5	#1, #5
	Yaw Angle	γ	°	-4	0	4	#1, #5
Opto-electrical	Power Conversion Efficiency	PCE	%	-	31	-	#1

Notes:


1. Tested under the following conditions: CW bias current, solder pad temperature: 25°C;
2. Linear regression between 90mA – 180 mA;
3. The range is from the left 10% of the maximum luminous intensity to the right one;
4. The threshold value is 10% of the maximum luminous intensity;
5. The position of light spot: 300mm from light source.

Electro-optic conversion curve



* All tests are under CW condition with gold pad temperature 25°C

Product Dimension(units:mm)



Overall size of the copper

本文件及其披露的任何数据的所有权均属于度巨核芯光电技术（苏州）有限公司，构成并包含专有信息。除非度巨核芯光电技术（苏州）有限公司明确书面授权，否则不具有任何接收或拥有本文件授予或转让复制、使用或披露本文件所含任何信息的权利。

DG

REV: A0

商业秘密 Confidential document

Eye safety and disclaimer

Security recommendations

Depending on the usage of the device, the module may emit highly concentrated invisible infrared light that is harmful to the human eye. Products containing these modules may be required to follow the safety precautions specified in IEC 60850-1 and IEC62471.

Product Disclaimer

Suzhou DoGain Laser Co., Ltd. and its employees shall not be liable for any errors, inaccuracies or incompleteness contained in any data sheet or any product-related information.

We make no representations or warranties as to the fitness of the Products for any particular purpose or whether to continue to manufacture any Products. To the fullest extent permitted by applicable law, Du Yu will not be liable for:

- 1.Any liability arising from the application or use of any of the products.
- 2.Any implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability. We hereby declare that we shall not be liable for any direct, indirect, consequential, punitive, special or incidental losses (including but not limited to financial profit or loss, business interruption or loss of information) arising out of compliance with or failure to comply with this document.

It is the customer's responsibility to verify that the properties of the particular product described in the product specification are suitable for use in specific application scenarios The parameters provided in the datasheet and/or specification may vary from application to application and performance may vary over time. All operating parameters, including typical parameters, must be confirmed for each application scenario by the customer's technical experts.

Customer will be solely responsible for all legal, regulatory and safety requirements relating to Customer's products, although information or support may be provided in connection with product applications.

This document does not grant any license to any intellectual property rights, whether express or implied, by estoppel or otherwise. DoGain reserves the right to change any of its products and accompanying documentation without prior notice.

Unless modified in the Terms of Sale, the Product Specification may not be extended, including, but not limited to, any warranties made herein.

Note:

No responsibility is assumed for the use of these products. The products can emit Class I~IV radiation and must be operated with extreme care. Avoid directly viewing the laser beam or exposure to specular reflections. Proper eye wear must be worn at all times when operating. VCSEL Chip in the modules are electrostatic-sensitive device and proper ESD protection is required for handling



本文件及其披露的任何数据的所有权均属于度亘核芯光电技术（苏州）有限公司，构成并包含专有信息。除非度亘核芯光电技术（苏州）有限公司明确书面授权，否则不具有任何接收或拥有本文件授予或转让复制、使用或披露本文件所含任何信息的权利。

DG

REV: A0

商业秘密 Confidential document