

Data Sheet

850nm Single Mode VCSEL TO46

Dogain Optoelectronic Technology(Suzhou)Co.,Ltd

PN: DG-VP-S850-2DT2

Rev. 1.0

Sep. 2025

Note: Customers represent that they have all the necessary expertise to create and implement their own safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions.

Product Introduction

Performance characteristics

DoGain's DG-VP-S850-2DT2 is an 850nm single mode vertical cavity surface emitting laser diode in TO46 package with integrated thermoelectric cooler, NTC and ESD protection for sensing and spectroscopic applications.

Key Features

- 850nm single mode emission
- Circular beam
- Low operation current
- TO46 with TEC, NTC and ESD protection diode
- RoHS compliant

Application


- Gas sensors
- High precise depth sensor
- Industrial speed and distance sensor

Electro-optical characteristics (25°C)

Parameters	Symbol	Min	Typical	Max	Units	Test Condition
Optical Output Power	P_{OP}	-	2	-	mW	I _{op} =5mA, T _s =25°C
Threshold Current	I_{th}	-	1.5	2	mA	T _s =25°C
Differential Resistance	R_s	50	-	200	Ω	T _s =25°C
Operating Voltage	V_{op}	-	-	2.4	V	I _{op} =5mA, T _s =25°C
Slope Efficiency	η_s	-	0.75	-	mW/mA	T _s =25°C
Wavelength	λ_{peak}	840	850	860	nm	I _{op} =5mA, T _s =25°C
Wavelength tuning with current	$\Delta\lambda/\Delta I$	-	0.35	-	nm/mA	T _s =25°C
Wavelength tuning over temperature	$\Delta\lambda/\Delta T$	-	0.07	-	nm/°C	-
Spectral Width (RMS)	$\Delta\lambda$	-	100	-	MHz	I _{op} =5mA, T _s =25°C
Side Mode Suppression Ratio	SMSR	10			dB	I _{op} =5mA, T _s =25°C
Beam Full Divergence (D86)	φ	-	20	-	°	I _{op} =5mA, T _s =25°C
TEC Current	I_{TEC}	-	-	500	mA	
NTC Thermistor Resistance	R_{NTC}	-	10	-	kΩ	T _s =25°C
NTC Thermistor B _{25/50} Value	B	-	3930	-	K	

* All tests are under CW condition with heatsink temperature 25°C

Product appearance mechanical characteristics



Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Operating Temperature	Top	-40	85	°C
Operating Humidity	Hop	0	85	%
Continuous Forward Current	I _f	-	2.5	mA
Continuous Reverse Current	I _r	-	10	mA
Soldering Temperature (less than 10s)		-	270	°C
Storage Temperature	T _s	-40	110	°C
Storage Humidity	H _s	0	85	%

Unless modified in the Terms of Sale, the Product Specification may not be extended, including, but not limited to, any warranties made herein.

Eye safety and disclaimer

Security recommendations

Depending on the usage of the device, the module may emit highly concentrated invisible infrared light that is harmful to the human eye. Products containing these modules may be required to follow the safety precautions specified in IEC 60850-1 and IEC62471.

Product Disclaimer

Dogain Optoelectronic Technology (Suzhou) Co., Ltd. and its employees shall not be liable for any errors, inaccuracies or incompleteness contained in any data sheet or any product-related information.

We make no representations or warranties as to the fitness of the Products for any particular purpose or whether to continue to manufacture any Products. To the fullest extent permitted by applicable law, DoGain will not be liable for:

1. Any liability arising from the application or use of any of the products.
2. Any implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability. We hereby declare that we shall not be liable for any direct, indirect, consequential, punitive, special or incidental losses (including but not limited to financial profit or loss, business interruption or loss of information) arising out of compliance with or failure to comply with this document.

It is the customer's responsibility to verify that the properties of the particular product described in the product specification are suitable for use in specific application scenarios. The parameters provided in the datasheet and/or specification may vary from application to application and performance may vary over time. All operating parameters, including typical parameters, must be confirmed for each application scenario by the customer's technical experts.

Customer will be solely responsible for all legal, regulatory and safety requirements relating to Customer's products, although information or support may be provided in connection with product applications.

This document does not grant any license to any intellectual property rights, whether express or implied, by estoppel or otherwise. DoGain reserves the right to change any of its products and accompanying documentation without prior notice. Unless modified in the Terms of Sale, the Product Specification may not be extended, including, but not limited to, any warranties made herein.

Note:

No responsibility is assumed for the use of these products. The products can emit Class I~IV radiation and must be operated with extreme care. Avoid directly viewing the laser beam or exposure to specular reflections. Proper eye wear must be worn at all times when operating. VCSEL Chip in the modules are electrostatic-sensitive device and proper ESD protection is required for handling.

