

High-power Single Emitter Diode Lasers, 792nm, 22W cw

792nm 22W高功率单管激光芯片


DG-UMC-500-792-TE-22-4.5

性能参数 Performance parameters	符号 Symbol	最小值 Minimum	典型值 Typical	最大值 Maximum	单位 Unit
Operation					
输出功率 Optical output power	P_o		22		W
中心波长 Wavelength	λ_c	789	792	795	nm
冷波长@2A Wavelength@2A	λ_0	7888	790	792	nm
工作模式 Operation mode			CW		
Geometrical					
发光区宽度 Emittier width	E.W.	495	500	505	μm
腔长 Cavity length	L	4495	4500	4505	μm
宽度 Width	W	695	700	705	μm
厚度 Thickness	D	105	115	125	μm
Electro Optical Data					
电光转换效率 Electro-optic conversion efficiency	η_c	55	58		%
斜率效率 Slope efficiency	SE	1.15	1.26		W/A
阈值电流 Threshold current	I_{th}		3.4	5	A
工作电流 Operating current	I_{op}		21	23	A
工作电压 Operating voltage	V_{op}		1.77	1.85	V
光谱宽度 Spectral width (FWHM)	$\Delta\lambda$		2	5	nm
波长温度系数 Wavelength temperature coefficient	$\Delta\lambda/\Delta T$		0.3		nm/°C
水平远场发散角 (95%E) Horizontal F.F. divergence angle	$\theta_{//}$		9	11	Deg
垂直远场发散角 (95%E) Vertical F.F. divergence angle	$\theta_{\perp}$		60	66	Deg
TE 偏振度@5A TE Polarization@5A		95.0	96.0		%

备注：本参数为产品进行COS封装，CW电流模式，导热板25°C条件下的测试参数。

Note: These parameters were obtained by testing COS packaged products in the CW mode at 25°C.

Power-Current-Voltage-Efficiency



Spectral characteristics

