

Datasheet (Preliminary)

VCSEL Array Substrate Module

Dogain Optoelectronic Technology(Suzhou)Co., Ltd

PN: DG-VP-M3-60BSA35

Rev. A.00

Nov. 2025

Note:

Customers represent that they have all the necessary expertise to create and implement their own safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions.

Revision History

Rev.	Effective Date	Revised By.	The Main Contents Revised.
A00	2025.08.29	马玉梅	Preliminary version released

Product Introduction

Performance characteristics

- Module material: substrate 3535
- Multimode output: The laser operates at 650nm 808nm 1064nm , independent laser or together laser
- Chip power: 650 20mw (1ea) , 808 20mw (1ea), 1064 10mw (2ea)
- Other wavelengths, chip dimensions, and emitter patterns are available according to customer request.

Application

- Consumer electronics
- Machine vision
- Infrared illumination
- Industrial applications
- Medical Beauty

Electro-optical characteristics (25°C)

650 20mw CW

TBD

* All tests are under CW condition with heatsink temperature 25°C

808 20mw CW

Parameters	Symbol	Min	Typical	Max	Units	Test Condition
Peak Power Output	P _{OP}	20	25	-	mW	CW 35mA 25°C
Threshold Current	I _{th}	8	10	15	mA	CW 35mA 25°C
Laser Forward Voltage	V _{op}	1.5	1.8	2.1	V	CW 35mA 25°C
Slope Efficiency	η _s	0.9	1	-	W/A	CW 35mA 25°C
Power Conversion Efficiency	PCE	35	37	-	%	CW 35mA 25°C
Peak Wavelength	λ _{peak}	800	808	816	nm	CW 35mA 25°C
Beam Angle 1/e ²	φ	21	24	27	°	CW 35mA 25°C
Max operating current	I _{max}			75	mA	CW 25°C



* All tests are under CW condition with heatsink temperature 25°C

1064 20mw CW



Parameters	Symbol	Min	Typical	Max	Units	Test Condition
Peak Power Output	P _{OP}	18	20	-	mW	CW 40mA 25°C
Threshold Current	I _{th}	4	6	8	mA	CW 40mA 25°C
Laser Forward Voltage	V _{op}	1.4	1.8	2.1	V	CW 40mA 25°C
Slope Efficiency	η _s	0.5	0.6	-	W/A	CW 40mA 25°C
Power Conversion Efficiency	PCE	28		-	%	CW 40mA 25°C
Peak Wavelength	λ _{peak}		1064		nm	CW 40mA 25°C
Beam Angle 1/e ²	φ		23		°	CW 40mA 25°C
Max operating current	I _{max}			50	mA	CW 25°C

* All tests are under CW condition with heatsink temperature 25°C

Electro-optic conversion





* All tests are under pulse condition on CW.



* All tests are under pulse condition on CW.

Product Dimension(units: mm)


Parameter	Ratings	Units
module Width	3.45 ± 0.1	mm
module Length	3.45 ± 0.1	mm
Anode Contact	Cu surface	/
module Thickness	0.9 ± 0.1	mm
Cathode Contact	Cu surface	/



Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Units
Operating temperature	Top	-20	60	°C
Operating humidity	Hop	0	85	%
Storage temperature	Ts	-20	60	°C
Storage humidity	Hs	0	85	%
Solder Reflow	cycle		5	

Reflow soldering charateristics



特制参数 Profile Feature	无铅焊料 Lead-Free Solder
平均上升速率 (T _{smax} 至 T _p) Average Ramp-Up Rate (T _{smax} to T _p)	3 °C/sec max.
预热: 温度最小值 (T _{smin}) Preheat: Temperature Min (T _{smin})	150
预热: 最高温度 (T _{smax}) Preheat: Temperature Max (T _{smax})	200
预热: 时间 (t _{smin} 到 t _{smax}) Preheat: Time (t _{smin} to t _{smax})	60-180 secs
回流温度 (T _L) Time Maintained Above: Temperature (T _L)	217°C
回流时间 (t _L) Time Maintained Above: Time (t _L)	60-150 secs
峰值/分类温度 (T _p) Peak/Classification Temperature(T _p)	255±5°C
实际峰值温度 (t _p) 在 5°C 以内的时间 Time Within 5°C of Actual Peak Temperature (t _p)	20~40 secs
降低速率 Ramp-Down Rate	5°C/sec max.

Eye safety and disclaimer

Security recommendations

Depending on the usage of the device, the module may emit highly concentrated invisible infrared light that is harmful to the human eye. Products containing these modules may be required to follow the safety precautions specified in IEC 60850-1 and IEC62471.

Product Disclaimer

Suzhou DoGain Laser Co., Ltd. and its employees shall not be liable for any errors, inaccuracies or incompleteness contained in any data sheet or any product-related information.

We make no representations or warranties as to the fitness of the Products for any particular purpose or whether to continue to manufacture any Products. To the fullest extent permitted by applicable law, DoGain will not be liable for:

- 1.Any liability arising from the application or use of any of the products.
- 2.Any implied warranties, including warranties of fitness for a particular purpose, non-infringement and merchantability. We hereby declare that we shall not be liable for any direct, indirect, consequential, punitive, special or incidental losses (including but not limited to financial profit or loss, business interruption or loss of information) arising out of compliance with or failure to comply with this document.

It is the customer's responsibility to verify that the properties of the particular product described in the product specification are suitable for use in specific application scenarios The parameters provided in the datasheet and/or specification may vary from application to application and performance may vary over



time. All operating parameters, including typical parameters, must be confirmed for each application scenario by the customer's technical experts.

Customer will be solely responsible for all legal, regulatory and safety requirements relating to Customer's products, although information or support may be provided in connection with product applications.

This document does not grant any license to any intellectual property rights, whether express or implied, by estoppel or otherwise. DoGain reserves the right to change any of its products and accompanying documentation without prior notice.

Unless modified in the Terms of Sale, the Product Specification may not be extended, including, but not limited to, any warranties made herein.

Dogain Optoelectronic Technology (Suzhou) Co., Ltd